



Practices Affecting Irrigation Ditches

The following regulations must be observed by those desiring to build bridges, crossings, install pipe, cut through ditches, install outlets or dams, install safety grates or otherwise create conditions that could affect the flow or control of water in ditches of the summit Creek Irrigation and Canal Company.

1. Any bridge installed over a ditch must be constructed and maintained in such a manner that:
 - A) It does not come into contact with the concrete or rock lining of the ditch.
 - B) The lowest point of the bridge, where extending over the ditch, is at least two inches higher than the lining of the ditch.
 - C) If the ditch is not lined, the bridge will not restrict the flow of water.
2. Pipe will be permitted in company ditches only if said pipe meets the requirements of the Irrigation Company and is installed according to their specifications. Permission must be obtained before installing the pipe.
3. Crossings (other than bridges), outlets, dams or other structures are not to be installed in any ditch without first obtaining approval from the Company.
4. Safety grates may be installed after obtaining permission from the Irrigation Company. Those installing safety grates must agree to keep them cleared of trash and debris to the extent that they will not cause the water to flow beyond the confines of the ditch.
5. Cutting, crossing, breaking through or otherwise disturbing ditches is not to be done without permission from the Irrigation Company.
6. I (we) have read and understand the above regulations and agree to abide by these requirements.

Signed: _____ Date: _____.